

The Manitowoc Company, Inc.

Regional headquarters

- Americas**
Manitowoc,
Wisconsin, USA
Tel: +1 920 684 6621

**Europe, Middle East,
Africa**
Dardilly, France -
TOWERS
Tel: +33 472 18 20 20

China
Shanghai, China
Tel: +86 21 6457 0066

Greater Asia-Pacific
Singapore
Tel: +65 6264 1188

Dubai, UAE
Tel: +971 4 8862677
- Shady Grove,
Pennsylvania, USA**
Tel: +1 717 597 8121

**Wilhelmshaven,
Germany - MOBILE**
Tel: +49 (0) 4421 294 01

Grove crane range

Pocket guide
ASME B30.5
Imperial/Metric



manitowoc.com

This document is non-contractual. Constant improvement and engineering progress make it necessary that we reserve the right to make specification, equipment, and price changes without notice. Illustrations shown may include optional equipment and accessories and may not include all standard equipment.

© 2023 The Manitowoc Company, Inc.
Form Number: Grove Range
04-025-1M-1023

Grove Crane Range

Special Applications

Grove continues to design and manufacture specialized military cranes for demanding schedules and ever changing environments. Whether a mission requires an all-terrain, rough-terrain, or carrydeck crane, Grove has the solution.



All-terrain cranes

Grove all-terrains combine truck crane highway speeds with the off-road performance characteristics of our MEGATRAK™ suspension. Travel speeds up to 55 mph (85 km/h) get you to the job quickly.

Model	Capacity	Main boom	Extension	Max
All-terrain				
GMK3050-3	55 USt / 50 t	131 ft / 40 m	26 ft / 8 m	167 ft / 51 m
GMK3060-2	65 USt / 60 t	131 ft / 40 m	29 ft - 49 ft / 8,7 m - 15 m	190 ft / 58 m
GMK3060L-1	65 USt / 60 t	158 ft / 48 m	29 ft - 49 ft / 8,7 m - 15 m	216 ft / 66 m
GMK4080L	85 USt / 80 t	197 ft / 60 m	29 ft - 49 ft / 8,7 m - 15 m	253 ft / 77 m
GMK4080-3	88 USt / 80 t	167 ft / 51 m	29.5 ft - 69 ft / 9 m - 21 m	246 ft / 75 m
GMK4090-1	100 USt / 90 t	167 ft / 51 m	29.5 ft - 69 ft / 9 m - 21 m	246 ft / 75 m
GMK4100L-2	115 USt / 100 t	197 ft / 60 m	36 ft - 84 ft / 11 m - 25,6 m	292 ft / 89 m
GMK5120L	130 USt / 120 t	216.5 ft / 66 m	32 ft - 79 ft / 9,8 m - 24 m	305 ft / 93 m
GMK5150-1	175 USt / 150 t	167 ft / 50,8 m	36 ft - 137 ft / 11,2 m - 41,8 m	315 ft / 96 m
GMK5150L-1	175 USt / 150 t	197 ft / 60 m	36 ft - 111 ft / 11,2 m - 33,8 m	318 ft / 97 m
GMK5150XL	175 USt / 150 t	225 ft / 68.7 m	31.5 ft - 79.1 ft / 9,6 m - 24 m	315 ft / 96 m
GMK5180-1	210 USt / 180 t	210 ft / 64 m	36 ft - 112 ft / 11 m - 34 m	331 ft / 101 m
GMK5200-1	240 USt / 200 t	210 ft / 64 m	36 ft - 112 ft / 11 m - 34 m	331 ft / 101 m
GMK5250L-1	300 USt / 250 t	230 ft / 70 m	39 ft - 121 ft / 12 m - 37 m	361 ft / 110 m
GMK5250XL-1	300 USt / 250 t	258 ft / 78,6 m	36 ft - 111 ft / 11 m - 33,8 m	357 ft / 109 m
GMK6300L-1	350 USt / 300 t	263 ft / 80 m	39 ft - 121 ft / 12 m - 37 m	393 ft / 120 m
GMK6400-1	450 USt / 400 t	197 ft / 60 m	39 ft - 259 ft / 12 m - 79 m	449 ft / 137 m
GMK7550	550 USt / 450 t	197 ft / 60 m	39 ft - 259 ft / 12 m - 79 m	449 ft / 137 m

Grove Crane Range

> Carrydeck cranes

Grove carrydeck cranes are perfect for plant maintenance and material handling jobs. Multi-mode steering and tight dimensions deliver easy maneuverability.



> Rough-terrain cranes

Grove rough-terrain cranes are designed to handle tough job site conditions. Inverted outrigger jacks, compact dimensions and four steering modes allow easy setup and on-site maneuvering.



> Telescoping crawler

The GHC series combines excellent gradeability and lift capacity with 100 percent pick and carry capability. Engineered for exceptional maneuverability, with rugged, heavy-duty crawler tracks and telescoping boom.



> Truck cranes

Grove truck cranes feature quick set-up, long reach, high capacity booms and highway speed travel capabilities. A front stabilizer is standard for 360° operation.



Model	 Capacity	 Main boom	 Extension	 Max
Carrydeck				
GCD09	9 USt / 8,1 t	33.2 ft / 10,1 m	12 ft / 3,6 m	48 ft / 14,6 m
GCD15	15 USt / 13,6 t	41 - 50 ft / 12,5 - 15,4 m	15 ft / 4,6 m	69.5 ft / 21,2 m
GCD20	20 USt / 18,0 t	54.5 ft / 16,6 m	15 ft - 25 ft / 4,6 - 7,6 m	86 ft / 26,2 m
GCD25	25 USt / 22,7 t	71 ft / 21,6 m	17 ft / 5,1 m	95 ft / 28,9 m



Rough-terrain				
RT530E-2	30 USt / 30 t	95 ft / 29 m	26 ft - 45 ft / 7,9 m - 13,7 m	146 ft / 45 m
RT540E	40 USt / 35 t	102 ft / 31 m	26 ft - 45 ft / 7,9 m - 13,7 m	154 ft / 47 m
GRT655	55 USt / 51 t	114.3 ft / 34,8 m	26 ft - 45 ft / 7,9 m - 13,7 m	170 ft / 51,8 m
GRT655L	55 USt / 51 t	141.2 ft / 43 m	26 ft - 45 ft / 7,9 m - 13,7 m	196 ft / 59,8 m
RT765E-2	65 USt / 60 t	110 ft / 34 m	33 ft - 96 ft / 10 m - 29,2 m	214 ft / 65,2 m
RT770E	70 USt / 65 t	138 ft / 42 m	33 ft - 76 ft / 10,1 m - 23,2 m	221 ft / 67,4 m
GRT880	80 USt / 80 t	134.5 ft / 41 m	33 ft - 76 ft / 10 m - 23 m	223.3 ft / 68 m
GRT8100-1	100 USt / 100 t	154.3 ft / 47 m	33 ft - 76 ft / 10 m - 23 m	239.4 ft / 72,9 m
GRT8120	120 USt / 120 t	197 ft / 60 m	34.5 ft - 57.6 ft / 10,5 m - 17,6 m	265 ft / 80,8 m
RT9130E-2	130 USt / 120 t	160 ft / 48,8 m	36 ft - 111 ft / 11 m - 34 m	279 ft / 85 m
GRT9165	165 USt / 150 t	205 ft / 62,5 m	36.7 ft - 84.6 ft / 11,2 m - 25,8 m	299 ft / 91,1 m



Telescoping Crawler				
GHC30	30 USt / 30 t	82.6 ft / 25,2 m	21.3 ft - 42.7 ft / 6,5 m - 13 m	131.9 ft / 40,2 m
GHC50	50 USt / 45 t	99.7 ft / 30,4 m	21.3 ft - 42.7 ft / 6,5 m - 13 m	149 ft / 45,4 m
GHC55	55 USt / 50 t	99.7 ft / 30,4 m	21.3 ft - 42.7 ft / 6,5 m - 13 m	149 ft / 45,4 m
GHC75	75 USt / 70 t	118.1 ft / 36 m	26.2 ft - 49.2 ft / 8 m - 15 m	172.9 ft / 52,7 m
GHC85	85 USt / 80 t	137.8 ft / 42 m	26.2 ft - 49.2 ft / 8 m - 15 m	199 ft / 60,7 m
GHC110	110 USt / 100 t	153.4 ft / 46,8 m	26.2 ft - 49.2 ft / 8 m - 15 m	210 ft / 64 m
GHC130	132 USt / 120 t	131.9 ft / 40,2 m	26.2 ft - 88.6 ft / 8 m - 27 m	229.7 ft / 70 m
GHC140	140 USt / 127 t	170.9 ft / 52,1 m	26.2 ft - 49.2 ft / 8 m - 15 m	229.7 ft / 70 m



Truck-mounted				
TMS500-2 (95 ft boom)	40 USt / 36 t	95 ft / 29 m	26 ft - 45 ft / 7,9 m - 13,7 m	102.2 ft / 31,2 m
TMS500-2 (102 ft boom)	40 USt / 36 t	102 ft / 31 m	26 ft - 45 ft / 7,9 m - 13,7 m	108.7 ft / 33,1 m
TMS875-2	75 USt / 75 t	128 ft / 39 m	34.5 ft - 83.8 ft / 10,5 m - 25,6 m	194.3 ft / 49,2 m
TMS800-2	80 USt / 80 t	128 ft / 39 m	34.5 ft - 83.8 ft / 10,5 m - 25,6 m	194.3 ft / 49,2 m
TMS9000-2	115 USt / 100 t	169 ft / 51,6 m	34.5 ft - 83.8 ft / 10,5 m - 25,6 m	263.4 ft / 80,3 m
TTS9000-2	115 USt / 100 t	169 ft / 51,6 m	34.5 ft - 83.8 ft / 10,5 m - 25,6 m	263.4 ft / 80,3 m

